




SOLISTA MAXI LED



The Solista MAXI is an enhancement of the standard Solista LED beacon which allows the user the choice between economy or performance. In the economy modes the Solista MAXI performs extremely efficiently requiring as little as 3mA, but it can be switched to attain much higher light outputs where visibility is the prime objective. For even greater effectiveness a double flash sequence can be selected.

- 3 USER SELECTABLE OUTPUT SETTINGS
- WIDE OPERATING VOLTAGE RANGE
- SYNCHRONISATION FLASH
- HIGH EFFICIENCY
- SINGLE OR DOUBLE FLASH
- LONG SERVICE LIFE
- HIGH RELIABILITY
- LOCKING BASES

Specification

Voltage	9 to 60Vdc (*1)
Current	3mA / 6mA / 15mA (user selectable)
Light source	LED
Light output	>0.5Cd / >1Cd / >3Cd (user selectable)
Flash rate	1Hz, single or double flash (User selectable)
Flash colour	Red, amber, white
Temperature	- 10°C to + 55°C
Monitoring	Reverse polarity
Protection	IP54 Shallow base IP65 Deep & U base
Construction	Base ABS FR Lens PC
Weight	0.1Kg
Lens colour	Clear

(*1) 110 / 230Vac when used with a Deep powered base.