



Pump protection relays (Without level sensors)

SINGLE PHASE PUMP PROTECTION

Underload protection by undercurrent

- Eliminates need for level sensors to detect dry running.
- For 1-phase motors from 3 to 16 A.
- Precise motor heating and cooling memory, reproduces its thermal image.
- Visual indication of tripping cause.
- Adjustable reset time for $I<$.

Suitable for 1-phase submersible pumps. By monitoring undercurrent it avoids problems caused by dry running, cavitation, etc.

The great advantage of the PS relay is that, without requiring any external detectors like level electrodes, it monitors the load of the motor and stops it before an expensive breakdown occurs.

PS 11-R



PROTECTION FUNCTIONS

- $I>$ Overload
- $I<$ Undercurrent
- $U>$ Overvoltage


PS 16-R




MODELS		PS 11-R	PS 16-R
Adjustment range Motor 400 V 50/60 Hz	I_B (A) CV kW	3 - 11 0,5 - 2 0,37 - 1,5	3 - 16 0,5 - 3 0,37 - 2,2
Code	according to the relay voltage supply (+15% -10%) ac: 50/60 Hz	230 Vac single phase 12164	230 Vac single phase 12163
		115 Vac single phase 12171	115 Vac single phase 12172

DIMENSIONS PS RELAY (mm)

PS 11-R




PS 16-R



CHARACTERISTICS	
Thermal memory / Overload trip	Yes / From 1,1 $\times I_B$
Maximum motor nominal voltage	230 Vac
Trip classes (IEC 947-4-1)	10
Undercurrent protection adjustable / Trip delay	From 0,4 to 0,9 $\times I_B$ / 5 s
Overvoltage protection	From nominal V + 15%
Reset mode for protection against dry running	$I<$ automatic (adjustable) and remote. More info in page 28
Reset mode for other protection functions	$I>$ automatic and remote, $U>$ automatic. More info in page 28
Signalling LED's	3 LED's: ON + $I>$ $I<$ + $U>$
Output contacts	1 relay with 1 NO
Switching power	I_{th} : 5A; AC15 - 250V - 2A; DC13 - 30V - 2A
Terminals: Max. section / screw torque	2,5 mm ² , No. 22 - 12AWG / 20Ncm, 1,8 LB - IN
Power consumption	PS11-R: 7 VA (230 Vac) - 4 VA (115 Vac) PS16-R: 3 VA (115-230 Vac)
Protection degree / weight / mounting	IP20 / 0,15 kg / DIN rail
Storage temperature	-30°C +70°C
Operation temperature / max. altitude	-15°C +60°C / 1000m; -15°C +50°C / 3000m
Standards	IEC 255, IEC 947, IEC 801, EN 50081-2
	CE

Settings and curves, see pages 24 to 29.

WIRING DIAGRAM (mm)



CARREL-ELECTRADE LIMITED

Auckland Tel: 09-525 1753
Fax: 09-525 1756

Christchurch Tel: 03-366 1242
Fax: 03-379 1991

Email: sales@carrel-electrade.co.nz
Web: www.carrel-electrade.co.nz