



## Power Supply EG I-130-MM Series 130 - Relay Output- MIN/MAX-Control

- To connect two 2 or 3-wire sensors in NO-function with NPN or PNP transistor output. When connecting antivalent sensors the NO-output can be connected.
- Integrated MIN/MAX-Control
- With one output relay (1 x changeover)

Certificate:



### Technical Data

Operating voltage ( $U_B$ )	115/230 V AC $\pm$ 15% 40...60 Hz
No-load current ( $I_0$ )	typ. 20mA
Output function	1 x potential-free change-over contact
Contact rating each relay max..	250 V AC/ 6 A
<b>Type</b>	<b>EGI-130-MM</b>
<b>Art.-No.</b>	<b>522 200</b>
<b>Connection drawing</b>	<b>see below</b>
Actuating voltage ( $U_s$ )	24 V DC $\pm$ 20%
Actuating current max. ( $I_s$ )	60 mA
Residual ripple acc. to DIN 41 755 max.	2 %
Actuating signal	pnp or npn
Permitted ambient temperature	-25...+80°C
Display	LED geen or yellow
Version	min./max. -Control
Degree of protection IEC 529	housing: IP 30 connections: IP 20
Connection	screw terminals

All specifications are subject to change without notice. (11/2004)

