



TIMBER MOISTURE METER ACCESSORIES



Sliding Hammer Electrode CSH102

Fitted with 60mm hardened steel needle probes with insulated shafts for taking gradient readings through a section of timber to a depth of 45mm.

Optional 45mm insulated needle probes will measure to a depth of 30mm

Dimensions 315mm long x 45mm dia.

Weight 1.5kg



Calibration Test Card

For checking resistance type timber moisture meter calibration.

Simply place the electrode needles or blades across the test pads and compare the readings with those shown on the card.

Calibration Reference: AS/NZS 1080.1:1997

Dimensions 76 x 57 x 10mm

Weight 55g

CARREL ELECTRADE LTD

MANUFACTURERS, IMPORTERS AND DISTRIBUTORS OF ELECTRICAL ENGINEERING PRODUCTS
POSTAL ADDRESS: P O BOX 11078, ELLERSLIE 1542, AUCKLAND NEW ZEALAND
FACTORY AND OFFICE: 661 GREAT SOUTH ROAD, PENROSE 1061
TELEPHONE: +64-9-525 1753 FACSIMILE: +64-9-525 1756
CHRISTCHURCH BRANCH: 73B BRISBANE STREET, SYDENHAM
TELEPHONE: 03-366 1242 FACSIMILE: 03-379 1991
EMAIL: sales@carrel-electrade.co.nz WEB: www.carrel-electrade.co.nz